


CX14 S2 1000X525 PLUS

SMALL SIZE, GREAT MANOEUVRABILITY



CX14

The new CX14 electric pallet trucks are compact, lightweight and easy to use. They have been specifically designed for use in confined spaces within rail, shops, supermarkets and on-board delivery vehicles. These simple and efficient pallet trucks are built to last and are perfect for all your pedestrian material handling needs. They are available in four different versions: BASIC, PLUS AGM, EVO AGM and EVO Li-ION (Lithium batteries).




INTELLIGENT TILLER

- Ergonomic tiller designed for both left and right handed operation.
- Butterfly valves for traction control.
- Safety push button with warning buzzer.
- Turtle function for moving in tight areas with the handle in vertical position while remaining almost within the profile of the machine.



TRACTION & SAFETY

Traction is granted by the biggest heavy-duty stabilizer wheels (100x40 mm) in the category, with heavy duty spring. All linkage connections done through bushings that increase stability and durability.




ON-BOARD BATTERY CHARGER

Built-in battery charger provides a convenient charging solution and eliminates the need to remove the battery from the machine.



RELIABILITY

- Robust frame (metal motor wheel protection 6 mm thick) designed to guarantee maximum durability and resistance to torsion and heavy loads.
- Battery discharge indicator to allow easy management.
- Easy access to electrical components for maintenance.




MANOEUVRABILITY

- Short chassis dimension (L2 = 410 mm) to offer improved manoeuvrability in confined spaces.
- Compact design perfect for working in narrow areas and corridors, featuring a tighter turning radius (Wa = 1345 mm) for faster pinwheeling and easier navigation in congested spaces.
- Smooth rounded fork tips and entry/exit rollers to optimize pallet handling.



ROLLERS

Standard configuration provided with single polyurethane rollers. Available tandem rollers as optional.



Description

1.1 Manufacturer	LIFTER		
Lift	ELECTRIC		
1.3 Drive	ELECTRIC		
1.4 Operator type	Pedestrian		
1.5 Load capacity	Q	Kg	1400
1.6 Load centre distance	c	mm	500
1.8 Load axle to end forks	x	mm	785
1.9 Wheel base	y	mm	1045

Weights

2.1 Service weight (battery included)	Kg	255
2.2 Axle load, laden rear	Kg	1052
2.2 Axle load, laden front	Kg	603
2.3 Axle load, unladen front	Kg	217
2.3 Axle load, unladen rear	Kg	38

Tyres/Chassis

3.1 Tyres: front wheels	RUBBER		
3.1 Tyres: stabilizers wheels - Front	POLY.C.		
3.1 Tyres: rear wheels	POLY.C.		
3.2 Tyre size: Steering wheels - Width	mm	76	
3.2 Tyre size: Steering wheels - Diameter	mm	250	
3.3 Tyre size: Load rollers - Diameter	mm	82	
3.3 Tyre size: Load rollers - Width	mm	80	
3.4 Tyre size: stabilizers wheels front - Diameter	mm	100	
3.4 Tyre size: stabilizers wheels front - Width	mm	40	
3.5 Tyre size: rear wheels - Q.ty (X=driven)	nr	2	
3.6 Tread, front	b10 mm	506	
3.7 Tread, rear	b11 mm	375	

Dimensions

4.4 Lift height	h3 mm	115
4.9 Height of tiller in drive position max	h14 mm	1242
4.15 Height, lowered	h13 mm	85
4.19 Overall length	l1 mm	1500
4.20 Length to face of forks	l2 mm	500
4.21 Overall width	b1 mm	720
4.22 Fork dimensions - Thickness	s mm	50
4.22 Fork dimensions - Width	e mm	150
4.22 Fork dimensions - Length	l mm	1000
4.25 Distance between fork arms	b5 mm	525
4.32 Ground clearance, centre of wheelbase	m2 mm	35
4.34 Aisle width	Ast mm	1700
4.35 Turning radius	Wa mm	1285

Performance data

5.1 Travel speed laden	Km/h	4.5
5.1 Travel speed unladen	Km/h	4.7
5.2 Lifting speed laden	m/s	0.02
5.2 Lifting speed unladen	m/s	0.03
5.3 Lowering speed laden	m/s	0.04
5.3 Lowering speed unladen	m/s	0.04
5.8 Max gradeability laden	%	5
5.8 Max gradeability unladen	%	10
5.10 Service brake		Electric

Electric motors

6.1 Drive motor power	kW	0.7
6.2 Lift motor power	kW	0.4
Battery Type	Tipo	TRACTION
6.4 Battery voltage	V	24
6.4 Battery capacity, Min	Ah	118
6.4 Battery capacity, Max	Ah	118
6.5 Battery weight, Min	Kg	78
6.5 Battery weight, Max	Kg	78

Integrated battery and battery charger

