

D45S-7, D50SC-7

Mast type	Maximum Fork Height	Maximum Lowered Height	Fully Extended Height	Free Lift	Rated Load Capacities							
					D45S-7, D50SC-7							
					Tilt Angle				Load Capacities			
					Single Pneumatics		Double Pneumatics		Single Pneumatics		Double Pneumatics	
With Load Backrest	With Load Backrest	FWD	BWD	FWD	BWD	LC 500mm	LC 600mm	LC 500mm	LC 600mm			
		deg	deg	deg	deg	kg	kg	kg	kg			
STD	3,000	2,230	4,420	160	8	10	8	10	5,000	4,570	5,000	4,570
	3,300	2,380	4,720	160	8	10	8	10	5,000	4,570	5,000	4,570
	3,650	2,555	5,070	160	8	10	8	10	5,000	4,570	5,000	4,570
	4,000	2,880	5,420	160	8	10	8	10	5,000	4,570	5,000	4,570
	4,250	3,005	5,670	160	8	10	8	10	5,000	4,570	5,000	4,570
	4,850	3,455	6,270	160	8	5	8	10	4,900	4,480	4,950	4,525
FF	3,000	2,210	4,400	860	8	10	8	10	5,000	4,575	5,000	4,575
FFT	4,000	2,090	5,415	740	8	8	8	8	5,000	4,585	5,000	4,585
	4,250	2,180	5,680	830	8	8	8	8	4,975	4,565	5,000	4,585
	4,700	2,330	6,130	980	8	8	8	8	4,800	4,400	4,850	4,450
	5,150	2,480	6,580	1,130	8	3	8	8	4,650	4,265	4,700	4,310
	5,600	2,630	7,030	1,280	8	3	8	5	4,500	4,125	4,550	4,175
	6,050	2,780	7,480	1,430	8	3	8	3	3,575	3,280	4,025	3,690

D50C-7, D55SC-7

Mast type	Maximum Fork Height	Maximum Lowered Height	Fully Extended Height	Free Lift	Rated Load Capacities							
					D50C-7, D55SC-7							
					Tilt Angle				Load Capacities			
					Single Pneumatics		Double Pneumatics		Single Pneumatics		Double Pneumatics	
With Load Backrest	With Load Backrest	FWD	BWD	FWD	BWD	LC 500mm	LC 600mm	LC 500mm	LC 600mm			
		deg	deg	deg	deg	kg	kg	kg	kg			
STD	2,750	2,230	4,170	170	8	10	8	10	5,500	5,030	5,500	5,030
	3,050	2,380	4,470	170	8	10	8	10	5,500	5,030	5,500	5,030
	3,400	2,555	4,820	170	8	10	8	10	5,500	5,030	5,500	5,030
	3,750	2,880	5,170	170	8	10	8	10	5,500	5,030	5,500	5,030
	4,000	3,005	5,420	170	8	10	8	10	5,500	5,030	5,500	5,030
	4,600	3,455	6,020	170	8	8	8	10	5,500	5,030	5,500	5,030
FF	2,875	2,210	4,275	870	8	10	8	10	5,500	5,035	5,500	5,035
FFT	3,875	2,090	5,290	750	8	8	8	8	5,500	5,050	5,500	5,050
	4,125	2,180	5,555	840	8	8	8	8	5,500	5,050	5,500	5,050
	4,575	2,330	6,005	990	8	8	8	8	5,375	4,935	5,425	4,980
	5,025	2,480	6,455	1,140	8	5	8	8	5,200	4,775	5,150	4,725
	5,475	2,630	6,905	1,290	8	3	8	5	4,650	4,270	4,750	4,360
	5,925	2,780	7,355	1,440	8	3	8	5	3,625	3,330	3,525	3,235

D55C-7

Mast type	Maximum Fork Height	Maximum Lowered Height	Fully Extended Height	Free Lift	Rated Load Capacities							
					D55C-7							
					Tilt Angle				Load Capacities			
					Single Pneumatics		Double Pneumatics		Single Pneumatics		Double Pneumatics	
With Load Backrest	With Load Backrest	FWD	BWD	FWD	BWD	LC 600mm	LC 600mm	LC 600mm	LC 600mm			
		deg	deg	deg	deg	kg	kg	kg	kg			
STD	2,750	2,230	4,170	170	8	10	8	10	5,500	5,500		
	3,050	2,380	4,470	170	8	10	8	10	5,500	5,500		
	3,400	2,555	4,820	170	8	10	8	10	5,500	5,500		
	3,750	2,880	5,170	170	8	10	8	10	5,500	5,500		
	4,000	3,005	5,420	170	8	10	8	10	5,500	5,500		
	4,600	3,455	6,020	170	8	8	8	10	5,400	4,900		
FF	2,875	2,210	4,275	870	8	10	8	10	5,500	5,500		
FFT	3,875	2,090	5,290	750	8	8	8	8	5,500	5,500		
	4,125	2,180	5,555	840	8	8	8	8	5,500	5,500		
	4,575	2,330	6,005	990	8	8	8	8	5,500	5,500		
	5,025	2,480	6,455	1,140	8	5	8	8	5,150	4,925		
	5,475	2,630	6,905	1,290	8	3	8	5	4,500	4,575		
	5,925	2,780	7,355	1,440	8	3	8	5	3,500	3,375		

Note : Mast Specifications & Rated Capacities are based on standard chassis with pneumatic tire and without side shifter.



- Production Subsidiary
- Sales Subsidiary
- Parts Depot Center



Doosan Industrial Vehicle Europe nv
 Europark-Noord 36A
 9100 Sint-Niklaas
 Belgium
 Tel.: +32 3 760 09 87
 Fax: +32 3 760 09 89
 Website: www.doosan-iv.eu

EUD45S7-180724ENV3 (July 2018)

Authorized Dealer



D35S-7 / D40S-7 / D45S-7 / D50C-7 / D55C-7
 D40SC-7 / D45SC-7 / D50SC-7 / D55SC-7

7 SERIES FORKLIFTS

Pneumatic Diesel 3.5 to 5.5 ton capacity
 Euro Stage IIIB / Euro Stage IV



